

## automatic water softeners

### water softeners with control

#### Autotrol 255/440 (timer)



1



2

#### Technical data:

throughput: 1500 l/h  
operating pressure: 2-8bar  
water temperature: 6-25°C  
supply: 230V AC

| fig. | part no. | connection | type | tank capacity (l) | resin amount (l) | salt amount/ regeneration (kg) | salt tank/capacity | capacity at 20°e (l) | ø x width x height (mm) |
|------|----------|------------|------|-------------------|------------------|--------------------------------|--------------------|----------------------|-------------------------|
| 4    | 530131   | ½"         | MINI | 12                | 9                | 1.5                            | 35                 | 1680                 | 310x430x660             |
| 5    | 530132   | ¾"         | MAXI | 26                | 15               | 2.7                            | 80                 | 3360                 | 310x430x1100            |

### water softeners with control

#### Autotrol 255/440 (volumetric)



1



2

#### Technical data:

throughput: 1500 l/h  
operating pressure: 2-8bar  
water temperature: 6-25°C  
supply: 230V AC

| fig. | part no. | connection | type | tank capacity (l) | resin amount (l) | salt amount/ regeneration (kg) | salt tank/capacity | capacity at 20°e (l) | ø x width x height (mm) |
|------|----------|------------|------|-------------------|------------------|--------------------------------|--------------------|----------------------|-------------------------|
| 1    | 530133   | ¾"         | MINI | 12                | 9                | 1.5                            | 35                 | 1680                 | 310x430x660             |
| 2    | 530134   | ¾"         | MAXI | 26                | 15               | 2.7                            | 80                 | 3360                 | 310x430x1100            |

### water softeners with control

#### Autotrol LOGIX 255/740 (Timer)



1



2



3

#### Technical data:

throughput: 1500 l/h  
operating pressure: 2-8bar  
water temperature: 6-25°C  
supply: 230V AC

| fig. | part no. | connection | type   | tank capacity (l) | resin amount (l) | salt amount/ regeneration (kg) | salt tank/capacity | capacity at 20°e (l) | ø x width x height (mm) |
|------|----------|------------|--------|-------------------|------------------|--------------------------------|--------------------|----------------------|-------------------------|
| 1    | 530808   | ½"         | GIX 5  | 5                 | 4                | 0.5                            | 10                 | 700                  | 225x355x535             |
| 2    | 530809   | ½"         | GIX 8  | 8                 | 5                | 1                              | 20                 | 1120                 | 245x480x560             |
| 3    | 530824   | ¾"         | GIX 12 | 12                | 8                | 1.5                            | 25                 | 1680                 | 290x400x665             |

## water softeners with control Autotrol 255/740 (timer)



| fig. | part no. | connection | type     | tank capacity (l) | resin amount (kg) | salt amount/ regeneration (l) | capacity at 20°e (l) | width x height (mm) |
|------|----------|------------|----------|-------------------|-------------------|-------------------------------|----------------------|---------------------|
| 1    | 530828   | ¾"         | RG 12 AT | 12                | 9                 | 1.5                           | 1500                 | 185x660             |
| 2    | 530829   | ¾"         | RG 16 AT | 16                | 12                | 2.0                           | 2100                 | 185x760             |
| 3    | 530830   | ¾"         | RG 20 AT | 20                | 16                | 3.5                           | 2900                 | 185x1060            |

| fig. | part no. | description    | length x width x height (mm) | fig. | part no. | description    | length x width x height (mm) |
|------|----------|----------------|------------------------------|------|----------|----------------|------------------------------|
| 4    | 530360   | salt tank 35kg | 320x320x440mm                | 5    | 530363   | salt tank 70kg | 320x320x890mm                |

## water softeners with control Autotrol 366/604 (timer)



| fig. | part no. | connection | type   | tank capacity (l) | resin amount (kg) | salt amount/ regeneration (l) | salt tank/capacity | capacity at 20°e (l) | ø x width x height (mm) |
|------|----------|------------|--------|-------------------|-------------------|-------------------------------|--------------------|----------------------|-------------------------|
| 1    | 530825   | ½"         | ISI 5  | 5                 | 4                 | 0.5                           | 10                 | 700                  | 225x350x415             |
| 2    | 530826   | ½"         | ISI 8  | 8                 | 5                 | 1                             | 20                 | 1120                 | 245x450x440             |
| 3    | 530827   | ¾"         | ISI 12 | 12                | 8                 | 1.5                           | 25                 | 1680                 | 285x400x550             |

## water softeners with control DM (timer), with mix valve



**ATTENTION:**  
Install with pre-filter only (530178, page 1563)

### Technical data:

throughput: 900 l/h  
operating pressure: 2-8bar  
water temperature: 8-15°C  
supply: 230V AC

| no. | part no. | connection | type | tank capacity (l) | resin amount (l) | salt amount/ regeneration (kg) | salt tank/capacity | capacity at 20°e (l) | ø x width x height (mm) |
|-----|----------|------------|------|-------------------|------------------|--------------------------------|--------------------|----------------------|-------------------------|
| 1   | 530158   | ¾"         | DM   | 8                 | 5.6              | 1                              | 10                 | 1000                 | 250x480x480             |