

Manual water softeners

water softeners with two valves



Technical data:

throughput: 1000 l/h
operating pressure: 1-8bar
water temperature: 4-25°C

fig.	part no.	connection	type	tank capacity (l)	resin amount (l)	salt amount/ regeneration (kg)	capacity at 20°e (l)	ø x width x height (mm)
1	530161	3/8"	DVA LT	5	3.5	0.5	700	190x255x300
2	530120	3/8"	DVA LT	8	5.6	1	1120	190x255x400
2	530199	3/4"	DVA LT	8	5.6	1	1120	190x255x400
3	530121	3/8"	DVA LT	12	8.4	1.5	1680	190x255x500
3	530201	3/4"	DVA LT	12	8.4	1.5	1680	190x255x500
4	530126	3/8"	DVA LT	16	11.2	2	2240	190x255x600
4	530202	3/4"	DVA LT	16	11.2	2	2240	190x255x600
5	530127	3/8"	DVA LT	20	14	2.5	2800	190x255x900
5	530203	3/4"	DVA LT	20	14	2.5	2800	190x255x900

water softeners with bypass valve and mix valve



Technical data:

throughput: 900 l/h
operating pressure: 1-8bar
water temperature: 4-25°C

fig.	part no.	connection	type	tank capacity (l)	resin amount (l)	salt/reg. (kg)	capacity at 20°e (l)	ø x width x height (mm)
1	530122	3/8"	DVA BP	8	5.6	1	1120	190x255x400
2	530123	3/8"	DVA BP	12	8.4	1.5	1680	190x255x500
3	530124	3/8"	DVA BP	16	11.2	2	2200	190x255x600
4	530125	3/8"	DVA BP	20	14	2.5	2800	190x255x900